

#### Features

- Support embedded Linux OS
- Support BNC and IPC Sync Input
- Support VGA ,HDMI,CVBS Sync video output
- VGA,HDMI image resolution Max to 1920\*1080
- Support HD preview, all channels support Main stream
- Support Zoom function of preview and playback
- Support event, playback, backup recording ,support picture playback and search
- Support One-key recording
- Support fast playback
- Support P2P
- Support 4/8/16/32 ch simultaneous playback



#### Specifications

Model	DVR5832L
<b>Video &amp; audio input</b>	
Analog video input	32PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
Audio input	8PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
<b>Video &amp; audio output</b>	
HDMI output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
CVBS output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
VGA output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
Audio output	1PCS RCA Port( line level , impedance : 1kΩ)
<b>Video &amp; audio code and decode parameters</b>	
Video compress standard	H.264
Video code resolution	CIF
Video frame rate	NTSC: 2~30FPS/S; PAL: 2~25FPS/S
Video code rate	256Kbps/384Kbps/512Kbps/640Kbps/768Kbps/1M/1.5M/2M
Code stream mode	combine streams/ video stream
Audio compress standard	ADPCM
Audio code rate	16kpbs
Dual-stream	YES



Synchronously playback channels	6CH
<b>Hard driver</b>	
Mode	2*SATA
HDD capacity	each port support max 4TB HDD
<b>External port</b>	
Voice intercom	NO
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
Serial port	1PCS RS485 Port
	1PCS RS232 Port
USB port	2*USB2.0
Alarm input	8
Alarm output	1

## Ordering Information

DVR-5816	16 Ch DVR H.264, 2D1, 2 HDD
DVR-9016	16 Ch DVR H.264, 16D1, 8 HDD, 16 Video loops
DVR-5832L	32 Ch DVR H.264

