

Features

- Supports Analogue and AHD Cameras.
- P2P function, a key to the Internet.
- Humanized design, easy to operate.
- Supports a variety of mobile devices.
- Gigabit Ethernet port (optional).
- HD video, HD playback.
- Support dual-stream.
- CMS centralized network.
- Management software, 256 free access



Specifications

Model	AHD3404S
Video & audio input	
Analog video input	4PCS BNC Port(Level: 1.0Vp-p, impedance: 75Ω)
Audio input	4PCS RCA Port(Level: 2.0Vp-p, impedance: 1kΩ)
Video & audio output	
HDMI output	1024x768, 1280x720, 1280x1024, 1920x1080p
CVBS output	1PCS BNC Port(Level: 1.0Vp-p, impedance : 75Ω)
VGA output	1024x768, 1280x720, 1280x1024, 1920x1080p
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Video & audio code and decode parameters	
Video compress standard	H.264
Vdieo code resolution	4CH 720P@100/120FPS; 2CH 720P@50/60FPS +2CH 960H @50/60FPS; 4CH 960H@100/120FPS
Playback resolution	720P @25/30FPS; 960H@100/200FPS
Video frame rate	NTSC: 2~30FPS/S; PAL: 2~25FPS/S
Video code rate	512Kbps/640kbps/768Kbps/1M/1.5M/2M/3M/4M
Code stream mode	combine streams/ video stream



The Power of ONE



Audio compress standard	ADPCM
Audio code rate	16kpbs
Dual-stream	YES
Synchronously playback channels	1/4CH
Hard driver	
Mode	1*SATA
HDD capacity	each port support max 4TB HDD
External port	
Voice intercom	Yes
Internet port	1PCS RJ45 10M / 100M adaptive Ethernet port
Serial port	1PCS RS485
USB port	2*USB2.0
Alarm input	NO
Alarm output	NO



Ordering Information

HS-AHD-3404S	4 Ch HD DVR, .8U
HS-AHD-3408S	8 Ch HD DVR, .8U
HS-AHD-3216S	16 Ch HD DVR, .1U



As a company of innovation, TVS Security reserves the right to change product specifications without notice. For the latest product specifications, visit TVS Security online www.tvssecurity.com or contact your TVS Security sales representative.