

HS-RB200

Smart Pan/Tilt Rotating Bracket

HS-RB200 perfectly work with our megapixel HD IP camera, Analogue cameras directly connect to the IP module's RS-485 wires, no need wiring, can be controlled by DVR/NVR / platform clients software / smart phone's clients software. Especially suitable for indoor, outdoor to change camera's visible range to be wide and improve definition.

Features

- 255° Horizontal and 60° Vertical rotate. Left and Right stop positions can be freely adjustable.
- Built-in Intelligent decoder, intelligent preset position, intelligent scan function.
- Can set 1 home position.
- Rotating speed is adjustable, 6°/ 12°/ 20° per second.
- DC 12V Input power, R-S485 control cable.
- Can be easily connected to HD camera's R-S485 and DC 12V output.
- Only 170mm length, easy to install, compatible with all kind HD camera and analog camera.
- Waterproof design, dust-proof and high temperature resistance, industrial level plastic material.



Specification

Horizontal rotate angle	255°
Vertical/ Tilt Rotate Angle	60°
Rotate speed	6°/ 12°/ 20° PAN & 9° Tilt
Limited position	Pan / Tilt limited position, Free adjustable
Limited position auto scan	3 level adjustable
Preset position	8 preset position
Preset position route	1 tour route, 3 level of rotate speed
fixed monitoring position	Yes
Control wire	RS 485
Manual homing feature	Yes
Interface	Power interface + RS485
Power input	DC 12V±5% / 100mA
Power consumption	0.9W
Work environment / <u>Humidity</u>	-25°C-55°C / <u>less than</u> 95% (no condensation)

Order Information

HS-RB200

SMART PAN TILT ROTATING BRACKET



As a company of innovation, TVS Security reserves the right to change product specifications without notice. For the latest product specifications, visit TVS Security online www.tvsssecurity.com or contact your TVS Security sales representative.