

TVS-207CM7 Fixed Focus Color

Dome Camera

The TVS™ Indoor Dome Camera provides outstanding video surveillance performance while offering a cost effective security solution. Equipped with 3.6mm lens and engineered for superior resolution, this camera delivers crisp, detailed images while being flexible enough to meet the demands of most indoor applications.

Small and lightweight, the TVS indoor dome camera represents a strong value for users looking for reliable security in smaller venues. With a 700 TVL, flicker free vide this camera is well-suited to secure a variety of applications including restaurants, retail and small business environments.

Specification

Image sensor: 1/3" DIS
Signal system: PAL/NTSC
Effective pixels: 720 (H) × 480 (V)
Min. illumination: 0.1 Lux @ (F1.2, AGC ON)
0.28 Lux @ (F2.0, AGC ON)
Shutter time: PAL: 1/25 s to 1/15,000 s
NTSC: 1/30 s to 1/15,000 s
Lens: 3.6 mm @ F2.0 (6 mm optional)
Angle of view: 70.6° (3.6 mm)
Angle adjustment Pan: 0 - 355°, Tilt: 0 - 90°,
Rotation: 0 - 355°
Day / night: Electronic
Horizontal resolution: 700 TVL
Synchronization: Internal synchronization
Video output: 1Vp-p composite output (75 Ω/BNC)
S/N ratio: More than 52 dB
Operating conditions -40 °C - 60 °C (-40 °F - 140 °F)
Humidity: 90% or less (non-condensing)
Power supply: 12 VDC ± 10%
Power consumption: Max. 1 W
Dimension: Φ 97.8 x 64.4 mm (Φ 3.85" x 2.54")
Weight: 300 g (0.66 lbs)



Standard features

- Superior image performance
- 700 TVL sensor resolution
- Sensitivity: 0.2 lux @ 2.0
- Lens 3.6mm
- Light weight plastic enclosure
- 12 VDC

Ordering Information

HSD-207CM7 Fixed Dome Camera CM Series (ASIA)

